

The most important purpose of the layer 3 switch is to speed up the data exchange within the large LAN, and the routing function is also for this purpose. It can do one route and multiple forwarding.

Configure Two-Tier core switches as a VSX pair for Layer 2 aggregation of the data center access switches, IP data center services, and routing to the main campus.

If your core switch is doing the routing, you don't need static routes on the DHCP server. When you define an IP helper for a vlan the switch will correctly route the packets to the DHCP server.

In this example, core switches set up a CSS that functions as the gateway for wired and wireless users on the entire network and is responsible for routing and forwarding of user services.

The decision on using IP routing and VRF routing in the core switch is a design choice that can provide performance advantages on inter VLAN routing within each VRF and the GRT.

In this guide we will be going over how to configure multiple VLANs with routing so that each VLAN has Internet access. We will be using a M4300-8X8F as the core switch with two M4250-8G2FX-PoE+ ...

I am unable to set the ASA as the default gateway on the core switches as they are on a different range. I normally point my edge switches to the core stack as the gateway and use the ...

Note, as you mention, running a dynamic routing protocol such as OSPF/EIGRP between the 4500 switches and the 2800 router is by far the best solution and anything else is really just a bit ...

In my research I'm getting mixed suggestions - Some say that core switches are for routing, when others say that core switches have to be as fast as possible and have minimal tasks dedicated to them.



Core Switch Configuration

Routing

Gateway

Web: <https://safireschools.co.za>

