

Connect all protection grounding for various devices jointly to a general grounding bar, and then to the same protection grounding bar in the room together with the protection ground (PGND) of the device.

Set up an FTP connection between the PC (FTP client) and the switch, enter the user name admin and password admin@huawei, and run the put command to upload the web page file to the switch.

Do not aerially route Ethernet cables outdoors. Keep signal cables more than 10 cm away from power cables. Ensure Ethernet cables have a stable environment.

A network cable of a category higher than Category 5 is recommended for the connection between electrical interfaces. Check whether the status of line pairs in cables is normal.

This document describes hardware installation procedures of the S9300, S9300E, and S9300X series switches, troubleshooting methods for common hardware faults, and switch maintenance instructions.

Connect the cable connectors to the ports, matching the numbers on the Ethernet cables to those on the ports. After connecting the cables, verify that they are all correctly connected.

To avoid electric shock or burn, remove conductive objects like jewelry and watch. Connect the ground cable first after installing the switch into a cabinet or rack. Do not remove the ground cable unless all ...

Route the Ethernet cables, arrange the cables in the cabinet, and then install cable connectors. Cable connectors made onsite must be securely attached and comply with related standards.

It also explains how to log in to your switch for the first time. The installation, cable connection, and login methods for most S series switches are similar. This guide uses the S5700-24TP-SI-AC as an ...



# Huawei Switch Connection Method

Network

Cable

Web: <https://safireschools.co.za>

