Uzbekistan 10km optical module

The XFP BiDi module features a highly reliable 1270nm DFB transmitter and 1330nm PIN photo-detector into single LC optical connector, which provides 10km link distance over single-strand single mode fiber.

It works to interconnect equipment with SFP+ model optical interfaces/ports to exchange and transmit data of up to 10Gbps over 10km. Through an optical cable or cord using 2 fibers, you will be able to ...

10GBASE-LR is a 10-gigabit Ethernet optical standard that operates at 1310 nm over single-mode fiber (SMF), supporting link distances of up to 10 km.

This product need to use in pair and match up with fiber converter and optical Ethernet switch with SFP slot, it can be used in Ethernet, telecom and optical fiber communication and other industries.

The SFP transceivers are high performance,cost effective modules supporting multi-rate of 10Gbps and 10km transmission distance with SMF.The transceiver consists of three sections:a FP laser ...

The SFP+ transceivers are high performance, cost effective modules supporting data rate of 10Gbps and 10km transmission distance with SMF. The transceiver consists of three sections: a DFB laser ...

The LS-BL553101-10C SFP transceivers are high performance, cost effective modules supporting data rate of 125Mbps/155Mbps and 10km transmission distance with SMF.

Operating at a wavelength of 1310nm, it supports long-distance data transmission up to 20 kilometers over single-mode fiber (SMF), making it ideal for metro networks, data center interconnects, and ...

The XFP BiDi module features a highly reliable 1270nm DFB transmitter and 1330nm PIN photo-detector into single LC optical connector, which provides 10km link ...

The SFP transceivers are high performance, cost effective modules supporting dual data-rate of 1.25Gbps/1.0625Gbps and 20km transmission distance with SMF.The transceiver consists of three ...

Web: https://safireschools.co.za